

Suction Buttom suction BA1

Datasheet

Description

Aerospa Whirlpool buttom suction type BA 1 is suitable for the most standard pop up waste systems.(such as Viega, Geberit...)

The up down function of the pop up waste will lift the plug (part 4/5) and open the drain function.

In the closed position, the water can be drawn from the pump.

The length of the pin at the plug can be cut that it fit to the pop up wast (depending on the popup-waste system)

One or two ways can be used as suction. Part 4 and part 5 must be adjusted to work properly by pulling it appart. Closing the pop-upwaste. Bring part 4 & 5 together and push it to the minimum level in the tub.





When supplied, both intake ports are closed.

Choose which opening is suitable for your use case and break it up with a hammer or other tool.





Technical Details

Descript	tion of components			φ 50 ₋₁
5	Escutcheon for cover:	Stainless steel, chrome plated		
5	Center part:	ABS		
4	Plug:	Fiberglass	(5) III	
4	O-Ring:	NBR	U	
3	Nut:	ABS		
3 2	Seal:	NBR		
1	Body:	ABS	4	200 \$
	Available colours:	chrome, white, g		
	Cuff:	ø50 mm (48 mm)		
	Hole:	2-ways possible ø52 mm	3	90
	Depth (behind the tub): Level (in the tub):	approx. 70mm approx. 30mm		Ψ - Φ 87,5 -
In combination with pop up waste and over flow				
	Art.Code chrome:	750-100-00-00		